

T. Ishida, et al.
U.S.S.N.: 10/036,184
Page 2

Amendments To The Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of claims:

1. (Presently Amended) An electrophotographic developer for use in steps where it is fed from a developer carrier to develop an electrostatic latent image on an electrostatically charged-image holder and where the above developed image is transferred onto a transferring material, wherein it is used for the electrostatically charged-image holder described above having a radius of curvature of 18 mm or less in a development effective range and is a two-component developer comprising a toner comprising at least a binder and a colorant and a carrier which is coated with a resin and has a weight average particle diameter of 40 to 100 μm ; the above toner has a volume average particle diameter of 8 to ~~11.5~~ 10.5 μm ; and the toner particles having a diameter of 6.35 μm or less account for 20 number % or less.
 2. (Original) The electrophotographic developer as described in claim 1, wherein a variation coefficient in toner particle size distribution in terms of number in the toner described above is 35 or less.
 3. (Cancelled).
-
4. (Original) The electrophotographic developer as described in any of claims 1 to 3, wherein a charging series of the toner described above has a negative charging property.
 5. (Original) The electrophotographic developer as described in any of claims 1 to 3, wherein the binder contained in the toner described above is a styrene base resin.

T. Ishida, et al.
U.S.S.N.: 10/036,184
Page 3

6. (Original) The electrophotographic developer as described in any of claims 1 to 3, wherein the carrier described above is an iron powder carrier.

7. (Original) The electrophotographic developer as described in any of claims 1 to 3, wherein the resin coating the carrier described above is a silicon resin.

8. (Presently Amended) An electrophotographic developer for use in steps where it is fed from a developer carrier to develop an electrostatic latent image on an electrostatically charged-image holder and where the above developed image is transferred onto a transferring material; wherein it is used for the electrostatically charged-image holder described above having a radius of curvature of 18 mm or less in a development effective range and is a two-component developer comprising a toner comprising at least a binder and a colorant and a carrier which is coated with a resin and has a weight average particle diameter of 40 to 100 μm ; the above toner has a volume average particle diameter of 8 to ~~11.5~~10.5 μm and the toner particles having a diameter of 6.35 μm or less account for 20 number % or less ~~wherein a variation coefficient in toner particle size distribution in terms of number in the toner described above is 35 or less; wherein the toner described above comprises toner particles having a diameter falling in a range of 4.00 to 5.04 μm in a range of 2 to 6 number % and toner particles having a diameter falling in a range of 5.04 to 6.35 μm in a range of 2 to 10 number %; and, wherein it is used for the electrostatically charged-image holder and the developer carrier which rotate in directions reverse to each other in the development effective range described above.~~

9-17. (Cancelled).